

## KVS-E88 Front

Rugged keyboard made of stainless steel for front panel mounting.



## Description

This keyboard has the layout of a standard keyboard. In order to save room, the NUM-Block was left out.

If the NUM-Block is needed, there is another version of this keyboard which you can find [HERE](#)

Like the other keyboards of the fullsize-range this keyboard is water- and dust proof to IP65 and has a good tactile feel due to the raised keycaps.

As frontpanel mounted version with integrated staybolts this keyboard can be easily integrated into an existing housing.

For further information you can go to the [main page](#) of this keyboard range.



**Specification****Mechanical data**

Housing:	Front-panel mounted with integrated studs
Housing:	High-Grade Steel
Degree of Protection:	IP65
Dimensions:	358,3 x 135,2 x 29 mm
Cable Length:	150 cm

---

**Keys**

Key Technology:	membrane
Number of Keys:	105
Keyboard Layout:	German
Operational Life:	10 mio. keystrokes min.
Stroke Force:	0,9 ± 0,2 N
Stroke Travel:	1,68 mm
Key Legend:	Laser

---

**Electric Data**

Interface:	<a href="#">PS/2</a>
------------	----------------------

---

**Environment**

Operating Temperature:	from -10 °C to +55 °C
Storage Temperature:	from -25 °C to +70 °C

---

Order No.	Article	
KV1222	KVS-E88-F-PS/2-DE	PS/2 Anschluß, deutsches Layout
KV1308	KVS-E88-F-PS/2-FR	PS/2 Anschluß, french Layout
KV1224	KVS-E88-F-PS/2-US	PS/2 interface, US layout

**sales@tastaturen.com Telefon: (0 81 42) 66 95 8-0 Fax: (0 81 42) 66 95 8-11**