

GFT-51-T-Touch integrated in a housing

Complete Standard Layout ideal for use under cramped conditions.



Description

- This desktop keyboard with integrated [Touchpad](#) is ideal for use extremely cramped areas as well as for applications needing a separate mouse device for data input.
-
- The compact keyboard covers the layout of a standard keyboard.
- The numerical and alphanumeric keys have individual RAL-colors to visually differentiate the input keys.
- The GFT-51 is ideal for alphanumeric code inputs for industrial, medical or laboratory purposes.

Features

- Membrane Keyboard with [USB](#) interface and integrated touchpad
- Customized solutions concerning form, color and [Design](#)
- Dust- and waterproof according to [IP 65](#) on the front
- The key mechanics of the GFT-51 is based on 9 mm metal dome including gold contacts. The metal dome key technology even allows a data input with gloves.



Specification

Mechanical data

Housing:	Polystyrene (HIPS)
Degree of Protection:	IP65
Dimensions:	183 x 111,5 x 11 mm

Keys

Key Technology:	metal dome
Number of Keys:	51
Keyboard Layout:	German or US
Operational Life:	1 mio. keystrokes min.
Actuation Force:	2 N
Stroke Travel:	0,3 mm
Key Legend:	silk screen

Electric Data

Interface:	USB or PS/2
------------	---




Operating Voltage: 5 V
 Operating Current: 4 mA

Environment

Operating Temperature: from 0 °C to +70 °C

Order No.	Article	
KS2231	GFT-51-T-Touch-USB-Ger	USB, German
KS2298	GFT-51-T-Touch-USB-US	USB, US
KS2337	GFT-51-T-Touch-PS2-Ger	PS/2, German
KS2368	GFT-51-T-Touch-PS2-US	PS/2, US

Links

Click!	Titel
	GFT-51-Tabletop Compact Industrial Keyboard Complete Standard Layout ideal for use in extremely cramped Application Areas.
	GFT-51-Matrix Membrane Keyboard Complete Standard Layout available with appropriate Controller and Housing
	GFT-51 Compact Membrane Keyboard with integrated Touchpad Complete Standard Layout available with appropriate Controller and Housing

sales@tastaturen.com **Telefon: (089) 89 43 99-0 Fax: (089) 89 43 99-11**